

Mr. SPEED



Since 1965



MANUFACTURERS & EXPORTERS
SUPERSPEED
E-mail : superspeedril@yahoo.com

+ 91 9915244777
+ 91 9915077778

First Time in India

Ching[®]
FLEXI
NO KINK



Garden Hose

Ching[®] Garden Hose was engineered with a lightweight Premium Hybrid Polymer to lie flat and eliminate kinking under pressure. It redefines flexibility, making it easy to maneuver around trees, bushes or other obstacles. Zero memory means your sprinkler stays put without twisting. And Ching[®] Garden Hose doesn't fight you when you coil it.

Features

- Extreme all-weather flexibility
- Will not kink under pressure
- No memory, lies flat, coils easily
- Lightweight, abrasion resistant

D/N	ID	OD	Work Pressure	Length
	mm	mm	bar	mtr
1/2"	12.5	16.8	8	25 / 50
3/4"	18.5	23.8	8	25 / 50
1"	25	31	8	25 / 50



PVC Transparent Reinforced Hose (Heavy Duty)



Application : Products are used for water supply & discharge, & also used to transport other fluids & gases in the field of industry, agriculture & construction, etc.

Feature : 1. Heavy weight, high transparency, good elasticity.
2. For high pressure water supply use.



D/N	I.D. (mm)	O.D. (mm)	Work Pressure		Burst Pressure		Weight kg/m	Length (mtr)
			bar	psi	bar	psi		
1/4"	6	12	20	300	60	900	0.12	25 / 50
1/4"	6	14	20	300	60	900	0.14	25 / 50
5/16"	8	14	20	300	60	900	0.13	25 / 50
3/8"	10	16	20	300	60	900	0.17	25 / 50
1/2"	12	18	20	300	60	900	0.20	25 / 50
3/4"	19	26	20	300	60	900	0.34	25 / 50
1"	25	32	20	300	60	900	0.42	25 / 50

PVC Heavy Duty Yellow Garden Hose



Application : Products are used for gardening , irrigation.

Feature : 1. The product is formed of three layers: inner soft PVC layer, outer layer made of high-transparency UV-resistant modified PVC and middle reinforced layer made of evenly-wound high strength polyester.
2. Colors is yellow, others available upon request.

Temperature : -40°C to + 90°C



D/N	ID mm	OD mm	Work Pressure		Length mtr
			bar	psi	
1/2"	12.5	16.8	8	115	25 / 50
3/4"	18.5	23.8	8	115	25 / 50
1"	25	31	8	115	25 / 50

Welding Hose 20 Bar (Oxygen + Acetylene)

IS : 447

 CM/L-9800023516



- Application** : For Oil/ Fuel / Water/ Air / Anti Freeze / Grease.
- Tube** : Seamless tube of vlend of natural and synthetic rubber compound resistant to fuel, oil, gas, oxygen and other non-combustible gases.
- Cover** : Plain or Fluted cover of TPR for lasting performance under server working conditions.
- Reinforcement** : High tensile, synthetic textile & filament yarn.
- Temperature** : -20°C ~ +80°C

D/N	Hose Inside Diameter	Hose Inside Diameter	Hose Outside Diameter	Work Pressure	Work Pressure	Length
inch	mm	mm	mm	bar	bar	mtr
6	1/4"	6.4	13.4	20	60	50 / 100
8	5/16"	7.9	15.0	20	60	50 / 100
10	3/8"	9.5	17.4	20	60	50 / 100

Thermo Plastic Fire Fighting Hose

TYPE 1 TYPE 2

IS : 12585

 CM/L-9800026118



- Application** : For use on fire fighting hose reels.
- Reinforcement** : High tensile, synthetic synthetic cords.
- Temperature** : -20°C ~ +75°C



D/N	I.D.	O.D.	Length
	(mm)	(mm)	(mtr)
3/4"	19.5	27	30/50
1"	25	33.5	30/50

PVC Orange Gas Hose

- Application** : Products are used to transport gas in housing & restaurant, etc.
- Feature** : This hose is flexible, elastic, and good air-tightness.

D/N	ID	OD	Work Pressure	Weight	Length	
	mm	mm	bar	kg/m	yard	mtr
5/16"	8	14	5	0.135	30 / 40 / 50	
3/8"	9	15	5	0.150	30 / 40 / 50	

PVC Yellow Sprayer Hose

- Application** : Products are suitable to transport compressed air for various pneumatic devices, compressor, generator parts, and mechanical maintenance, meanwhile, it is an ideal conveyance hose for agriculture chemical spray and civil engg.
- Feature** : Adopting unique formula of polyester reinforced PVC brings Flexibility and other advantages like abrasion-resistance, Corrosion-resistance, low temperature-resistance and bend-resistance to the product. The middle reinforced layer is made of high grade polyester fibre, thus giving the product extra high working pressure.

Size	I.D. X O.D.	Burst Pressure	Weight	Length
(inch)	(mm)	bar	kg/m	(mtr)
5/16"	8 X 14	150	0.14	50 / 100
3/8"	10 X 16	150	0.164	50 / 100
1/2"	13 X 19	150	0.226	50 / 100

PVC Reinforced Clear Hose (Medium Quality)



- Application** : Products are used for water supply and discharge, and also used to transport other fluids and gases in the field of industry, agriculture and construction etc.
- Feature** : 1. Light weight, high transparency, good elasticity.
2. For ordinary water supply use.

D/N	ID	OD	Work Pressure	Length
	mm	mm	bar	
1/4"	6	9	2	50 Yds
5/16"	8	11	2	50 Yds
3/8"	10	13	2	50 Yds
1/2"	13	16	2	25 / 50 Yds
3/4"	19	24	2	25 / 50 Yds
1"	24	28	2	25 / 50 Yds

PVC Yellow Garden Hose



- Application** : Products are used to transport gas in housing & restaurant, etc.
- Feature** : 1. The product is formed of three layers: inner soft PVC layer, outer layer made of high-transparency UV-resistant modified PVC and middle reinforced layer made of evenly-wound high strength polyester.
2. Colors is Yellow, others available upon request.

D/N	I.D.	O.D.	Length
	(mm)	(mm)	
1/2"	13	17	25 / 50 Yds
3/4"	19	24	25 / 50 Yds
1"	25	30	25 / 50 Yds

PVC Green Garden Hose



- Application** : Products are used to transport gas in housing & restaurant, etc.
- Feature** : 1. The product is formed of three layers: inner soft

D/N	I.D.	O.D.	Work Pressure	Length
	(mm)	(mm)	bar	
1/2"	13	17	2	25 / 50 Yds
3/4"	19	24	2	25 / 50 Yds
1"	25	30	2	25 / 50 Yds

PVC Clear Level Hose (Medium Quality)



Application

: Products are suitable for low pressure liquid supply and discharge and level measurement.

Feature

: Single Layer Structure, Light Weight, Flexible, Elastic, High Transparency.

Colours Available on request



Size	ID x OD	Standard
inch	mm	length
1/4"	6 X 8	10/50 Mtrs
5/16"	8 X 10	10/50 Mtrs
3/8"	10 X 12	10/50 Mtrs
1/2"	12 X 15	50 Mtrs
3/4"	19 X 22	50 Mtrs
1"	24 X 28	50 Mtrs

PVC Black Zebra Hose

Black Zebra



Application

: Products are used to transport water in housing & restaurant, etc.

D/N	I.D.	O.D.	Work Pressure	Length
	(mm)	(mm)	bar	
1/2"	13	17	2	25 / 50 Yds
3/4"	19	24	2	25/50 Yds
1"	25	30	2	25/50 Yds
1.1/4"	32	34	2	25 MTRS
1.1/2"	38	40	2	25 MTRS
2"	50	59	2	25 MTRS

PVC Yellow Garden Hose

DD Yellow



Application

: Products are used to transport water in housing & restaurant, etc.

D/N	I.D.	O.D.	Work Pressure	Length
	(mm)	(mm)	bar	
1/2"	13	17	2	25 / 50 Yds
3/4"	19	24	2	25/50 Yds
1"	25	30	2	25/50 Yds
1.1/4"	32	34	2	25 MTRS
1.1/2"	38	40	2	25 MTRS
2"	50	59	2	25 MTRS